



- NOTES:
1. ALL EXPOSED DOOR & VESTIBULE SURFACES FINISHED IN STAINLESS STEEL.
  2. SECURITY BARRIER FOR DOOR AND VESTIBULE ARE CONSTRUCTED OF FIBER REINFORCED CONCRETE.
  3. DESIGNED, MANUFACTURED AND TESTED IN ACCORDANCE WITH UL STANDARD UL608 (CERTIFICATION BP6254).
  4. STANDARD DAY GATE IS CONSTRUCTED OF CLEAR ANODIZED EXTRUDED ALUMINUM PROFILES AND GRAY ACRYLIC WITH ADA COMPLIANT LEVER LOCK SET IN US26D FINISH.
  5. VESTIBULE IS DESIGNED FOR GROUTLESS INSTALL. IT IS TO BE WELDED TO MODULAR VAULT PANELS, 1" WELD EVERY 12" MINIMUM. FULL WELD IS RECOMMENDED.
  6. SHIPPING WEIGHT IS 4,000 LBS.
  7. VESTIBULE IS CAST WITH TWO LIFT POINTS AT TOP. REQUEST (P/N 9040-0002) 3/4" T-12 LIFTING SWIVEL AND (P/N 9040-0006) 3/4"x 4" COIL BOLT FOR PROPER RIGGING ATTACHMENT.
  8. DOOR REQUIRES INSTALL KIT FOR PROPER INSTALLATION. REQUEST (P/N 102-2200).

**CAUTION!**  
**ONLY PROFESSIONALS EXPERIENCED**  
**AND QUALIFIED IN THE INSTALLATION**  
**OF MODULAR VAULTS AND VAULT**  
**DOORS SHOULD INSTALL THIS**  
**PRODUCT.**



**www.AmericanVault.us**

PRODUCT APPLICATION DRAWING  
 100 SERIES VAULT DOOR CLASS 1  
 MODEL 101-01 LS SHOWN  
 MODEL 101-02 RS OPPOSITE

SIZE	DWG NO	DATE	SHEET
A	20085	01.06.2014	1 OF 1