



NOTES:

1. ALL EXPOSED DOOR & VESTIBULE SURFACES FINISHED IN STAINLESS STEEL.
2. SECURITY BARRIER FOR DOOR AND VESTIBULE ARE CONSTRUCTED OF FIBER REINFORCED CONCRETE.
3. DESIGNED, MANUFACTURED AND TESTED IN ACCORDANCE WITH UL STANDARD UL608 (CERTIFICATION BP6254).
4. STANDARD DAY GATE IS CONSTRUCTED OF CLEAR ANODIZED EXTRUDED ALUMINUM PROFILES AND GRAY ACRYLIC WITH ADA COMPLIANT LEVER LOCK SET IN US26D FINISH.
5. VESTIBULE IS DESIGNED FOR GROUTLESS INSTALL. IT IS TO BE WELDED TO MODULAR VAULT PANELS, 1" WELD EVERY 12" MINIMUM. FULL WELD IS RECOMMENDED.
6. SHIPPING WEIGHT IS 6,500 LBS.
7. VESTIBULE IS CAST WITH TWO LIFT POINTS AT TOP. REQUEST (P/N 9040-0002) 3/4" T-12 LIFTING SWIVEL AND (P/N 9040-0006) 3/4"x 4" COIL BOLT FOR PROPER RIGGING ATTACHMENT.
8. DOOR REQUIRES INSTALL KIT FOR PROPER INSTALLATION. REQUEST (P/N 102-2200).

CAUTION!
 ONLY PROFESSIONALS EXPERIENCED
 AND QUALIFIED IN THE INSTALLATION
 OF MODULAR VAULTS AND VAULT
 DOORS SHOULD INSTALL THIS
 PRODUCT.



American Vault.us

PRODUCT APPLICATION DRAWING
 100 SERIES VAULT DOOR CLASS 3
 MODEL 103-01 LS SHOWN
 MODEL 103-02 RS OPPOSITE

SIZE	DWG NO	DATE	SHEET
A	20087	01.06.2014	1 OF 1