



CAUTION!
 ONLY PROFESSIONALS EXPERIENCED AND QUALIFIED IN THE
 INSTALLATION OF MODULAR VAULTS AND VAULT DOORS
 SHOULD INSTALL THIS PRODUCT.

- NOTES:
1. ALL EXPOSED DOOR & VESTIBULE SURFACES FINISHED IN STAINLESS STEEL.
 2. SECURITY BARRIER FOR THE DOOR AND VESTIBULE ARE CONSTRUCTED OF FIBER REINFORCED CONCRETE.
 3. DESIGNED, MANUFACTURED AND TESTED IN ACCORDANCE WITH UL STANDARD UL608 (CERTIFICATION BP6254).
 4. STANDARD DAY GATE IS CONSTRUCTED OF CLEAR ANODIZED EXTRUDED ALUMINUM PROFILES AND GRAY ACRYLIC WITH ADA COMPLIANT LEVER LOCK SET IN US26D FINISH.
 5. VESTIBULE IS DESIGNED FOR GROUTLESS INSTALL. IT IS TO BE WELDED TO MODULAR VAULT PANELS, 1" WELD EVERY 12" MINIMUM. FULL WELD IS RECOMMENDED.
 6. SHIPPING WEIGHT IS 3,600 LBS.
 7. VESTIBULE IS CAST WITH TWO LIFT POINTS AT TOP. REQUEST (P/N 9040-0002) 3/4" T-12 LIFTING SWIVEL AND (P/N 9040-0006) 3/4"x 4" COIL BOLT FOR PROPER RIGGING ATTACHMENT.
 8. DOOR REQUIRES INSTALL KIT FOR PROPER INSTALLATION. REQUEST (P/N 102-2200-36).

DO NOT SCALE

American
vault® Waco Texas

PRODUCT APPLICATION DRAWING
 100 SERIES VAULT DOOR, CLASS 1, 36"x80"
 MODEL 122-1-3680LS SHOWN
 MODEL 122-1-3680RS OPPOSITE



SIZE	DWG NO	DATE	SHEET
A	20214	12.01.2023	1 OF 1