



**CAUTION!**  
 ONLY PROFESSIONALS EXPERIENCED AND QUALIFIED IN THE  
 INSTALLATION OF MODULAR VAULTS AND VAULT DOORS  
 SHOULD INSTALL THIS PRODUCT.

**NOTES:**

1. ALL EXPOSED DOOR & VESTIBULE SURFACES FINISHED IN STAINLESS STEEL.
2. SECURITY BARRIER FOR THE DOOR AND VESTIBULE ARE CONSTRUCTED OF FIBER REINFORCED CONCRETE.
3. DESIGNED, MANUFACTURED AND TESTED IN ACCORDANCE WITH UL STANDARD UL608 (CERTIFICATION BP6254).
4. DAY GATE CONSTRUCTION IS SUBJECT TO CHANGE.
5. VESTIBULE IS DESIGNED FOR GROUTLESS INSTALL. IT IS TO BE WELDED TO MODULAR VAULT PANELS, 1" WELD EVERY 12" MINIMUM. FULL WELD IS RECOMMENDED.
6. SHIPPING WEIGHT IS APPROXIMATELY 6,500 LBS. (SUBJECT TO CHANGE)
7. VESTIBULE IS CAST WITH TWO LIFT POINTS AT TOP. REQUEST (P/N 9040-0002) 3/4" T-12 LIFTING SWIVEL AND (P/N 9040-0006) 3/4"x 4" COIL BOLT FOR PROPER RIGGING ATTACHMENT.
8. DOOR REQUIRES INSTALL KIT FOR PROPER INSTALLATION. REQUEST (P/N 102-2200-60).

**DO NOT SCALE**

**American Vault<sup>®</sup> Waco Texas**

PRODUCT APPLICATION DRAWING  
 100 SERIES VAULT DOOR, CLASS 2, 60"x96"  
 MODEL 122-2-6096LS SHOWN  
 MODEL 122-2-6096RS OPPOSITE



SIZE	DWG NO	DATE	SHEET
<b>A</b>	20219	12.01.2023	1 OF 1